

PF OUTSIDE CORNER FLASHING

Wall System Flashing Accessory

MANUFACTURER

Polyguard Products, Inc.
Ennis, TX 75119
(214) 515-5000
www.polyguard.com


PRODUCT DESCRIPTION

The PF Outside Flashing Corner is a 40-mil combination of rubberized asphalt bonded to polyethylene. The adhesive surface is covered with a release liner.

Liquid Adhesive is used to prepare surfaces for PF Corners.

Basic Uses

The PF Outside Flashing Corner provides maximum protection against moisture infiltration at outer corners. It bridges the flashing where it terminates, forming a continuous water deterrent seal. PF Corners can be used wherever a continuous water seal around outer corners is desired.



Advantages

At present, flashing around corners requires a series of cuts, folds, flaps and patching with Detail Sealant PW™. This is a time consuming, difficult procedure which often results in a less than desirable corner condition.

PF Corners offer an easy and practical method of field installation, eliminating as much as 10 minutes (per corner) of expensive field labor time. But most important, the design provides maximum protection against water penetration at outside corner conditions.

TECHNICAL DATA

Polyguard Products, Inc. provides design data and installation instructions to architects, engineers, specifiers, and contractors.

INSTALLATION

Surface Preparation: Clean all surfaces of dust, dirt and foreign matter. Eliminate sharp protrusions, which may puncture membrane. Surfaces should be dry prior

to application of 650 LT Liquid Adhesive and PF Corners.

Application of Corner: Remove silicone release liner and apply to properly prepared surface. Then apply Thru Wall Flashing Membrane over lapping 2-inches onto the PF Corner or End Dam. All vertical terminations must be sealed immediately with a tooled bead of Detail Sealant PW™.

LIMITATIONS

Thru Wall Flashing Components are recommended for concealed applications behind brick, marble, granite, siding or other exterior wall covering system. Polyguard Membranes should be covered within 30 days to prevent prolonged exposure to sunlight.

STORAGE/HANDLING

Thru Wall Flashing Systems components should be unloaded and stored in such a manner that prevents injury to the materials.

SAFETY

SDS sheets for all Polyguard products can be obtained at our website www.polyguard.com. Call Polyguard Products, Inc. at 214.515.5000 with questions.

WARRANTY

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product are beyond our control; such as weather, workmanship, equipment utilized and prior condition of the substrate. We will replace at no charge product proved to be defective within twelve (12) months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. A five (5) year material or system warranty may be available upon request. Contact Polyguard Products, Inc. for further details.

TECHNICAL SERVICES

Technical assistance, information and Polyguard's products are available through a nationwide network of distributors and architectural representatives, or contact Polyguard Products, Inc.

P.O. Box 755, Ennis, TX 75120-0755

Sales: (615) 217-6061 • Tech Support: (214) 515-5000

Email: archtech@polyguard.com

Website: www.polyguard.com

PACKAGING	PART NUMBER	UNIT SIZE
PF OUTSIDE CORNER	CORNEROUT7X7X8	7" x 7" x 8"

DISCLAIMER: The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.