

1. IDENTIFICATION

Product identifier**Product Name** Polyguard ClearBond Liquid Adhesive**Other means of identification****SDS #****UN/ID No** UN1139**Recommended use of the chemical and restrictions on use****Recommended Use** Adhesive used to promote adhesion of Polyguard Products' membranes.**Details of the supplier of the safety data sheet****Supplier Address**Polyguard Products INC.
4101 South Interstate 45
P.O. Box 755
Ennis, TX 75119**Emergency telephone number****Company Phone Number**

214-515-5000

Emergency TelephoneCHEMTREC 1-800-424-9300 (North America)
1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Appearance Clear-yellowish liquid**Physical state** Liquid**Odor** Hydrocarbon**Classification**

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Signal Word**Danger****Hazard statements**Causes skin irritation
Causes serious eye irritation
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof equipment
 Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 If skin irritation occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinguishment.

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Toluene	108-88-3	30-35
Hexane	110-54-3	30-35

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Seek medical attention if irritation develops or persists.
Ingestion	Immediately call a poison center or doctor/physician. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms	Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2). Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Do not use water in a jet.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous combustion products Carbon dioxide (CO2). Carbon monoxide.

Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak.
-----------------------------	--

For Emergency Responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Large spill: Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Use explosion proof equipment. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Materials Oxidizing materials. Acids. Alkalis.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Wear safety glasses with side shields (or goggles). Refer to 29 CFR 1910.133 for eye and face protection regulations.
- Skin and Body Protection** Wear protective gloves and protective clothing. Flame retardant antistatic protective clothing. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
- Respiratory Protection** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Hydrocarbon
Appearance	Clear- Yellowish liquid	Odor Threshold	Not determined
Color	Clear- Yellowish		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	No data available		
Melting point / freezing point	No data available		
Initial boiling point and boiling range	67 °C / 152.6 °F		
Flash point	-19.4 °C / -2.9 °F	(Tagliabue)	
Evaporation Rate	4.5 (ether (anhydrous) = 1)		
Flammability (Solid, Gas)	Liquid-Not applicable		
Flammability Limit in Air			
Upper flammability or explosive limits	7.5%		
Lower flammability or explosive limits	1.2%		
Vapor Pressure	20.3 kPa (152 mm Hg) [room temperature]		
Vapor Density	3.5	(Air=1)	
Relative Density	0.9		
Water Solubility	Partially soluble		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Autoignition temperature	No data available		
Hyphen	Not determined		
Kinematic viscosity	51-56 KU		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		
<u>Other information</u>			
VOC Content	527 g/l		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid all possible sources of ignition, spark or flame. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials

Oxidizing materials. Acids. Alkalis.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Inhalation May be harmful if inhaled.

Ingestion Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Carcinogenicity Group 3 IARC components are "not classifiable as human carcinogens".

Chemical name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		

Legend

*IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

Reproductive toxicity	Suspected of damaging fertility or the unborn child.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50	6,174.90 mg/kg
Dermal LD50	6,530.20 mg/kg
ATEmix (inhalation-vapor)	287.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Toluene 108-88-3	EC50: >433mg/L (96h, Pseudokirchneriella subcapitata) EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h, Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata)	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)
Hexane 110-54-3		LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Toluene 108-88-3	2.73
Hexane 110-54-3	4

Other adverse effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Toluene 108-88-3	Toxic Ignitable
Hexane 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1139
Proper Shipping Name Coating solution
Transport hazard class(es) 3
Packing Group II
Reportable Quantity (RQ) 2999.4 lbs / 1361.7 kg [399.7 gal / 1513 L]
Marine Pollutant Yes.

IATA

UN number or ID number UN1139
Proper Shipping Name Coating solution
Transport hazard class(es) 3
Packing group II

IMDG

UN number or ID number UN1139
Proper Shipping Name Coating solution
Transport hazard class(es) 3
Packing Group II
Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AIIC
Toluene	X	ACTIVE	X	X	X	X	X	X	X
Hexane	X	ACTIVE	X	X	X	X	X	X	X
Polystyrene-block-polyisoprene-block-polystyrene	X	ACTIVE	X		X	X	X	X	X
1,3-butadiene-styrene block polymer	X	ACTIVE	X		X	X	X	X	X

Legend:

- TSCA* - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL* - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS* - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS* - Japan Existing and New Chemical Substances
- IECSC* - China Inventory of Existing Chemical Substances
- KECL* - Korean Existing and Evaluated Chemical Substances
- PICCS* - Philippines Inventory of Chemicals and Chemical Substances
- AICS* - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Hexane 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	30-35	1.0
Hexane - 110-54-3	110-54-3	30-35	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental
Hexane - 110-54-3	Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Toluene 108-88-3	X	X	X
Hexane 110-54-3	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health hazards	Flammability	Instability	Special hazards
	-	-	-	-
<u>HMIS</u>	Health hazards	Flammability	Physical hazards	Personal Protection
	-	-	-	Not determined

Issue Date: 10-Feb-2023
Revision Date: 10-Feb-2023
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet